

## Description

The DynaEnergetics Pressure Release Sub allows users to equalize pressure between the annulus and tubing conveyed perforating string; commonly this is used in pressure testing production packers. The Kobe sub is placed below the production packer and above the differential sub when using a mechanical firing head. A hollow pin, once broken with wireline-deployed logging tools, allows equalization of pressure between the tubing string and annulus.



## Features

- Face seal between head of pin and sub body ensures the most reliable seal possible.
- Incorporates a Teflon seal ring contained in female EUE threads for greater sealing reliability.
- Additional sizes available upon request

## Specifications

Nominal Size	60 mm / 2 3/8"	73 mm / 2 7/8"
Part number	2317784	2317785
Weight	2 kg / 4.4 #	3.3 kg / 7.28 #
Overall Length	165 mm / 6.5"	177.8 mm / 7.0"
Maximum OD	77.8 mm / 3.063"	93.2 mm / 3.668"
No-Go ID	50.7 mm / 1.995"	62 mm / 2.441"
Temperature Rating	Varies with elastomer; 204°C with standard Viton seal	
Pressure Rating	68.9 MPa / 10,000 PSI	
Tensile	53 250 kg / 117 400 #	73 980 kg / 163 100 #
Connections	2 3/8" EUE box up, pin down	2 7/8" EUE box up, pin down
Redress Kit	2317786	2317787
Material	4140 HTSR	

**Note:** Product condition must be monitored, inspected and maintained regularly to ensure proper service in accordance with DynaEnergetics guideline. Failure to do so may result in personal injury and/or property damage. For questions please contact your DynaEnergetics representative.